FastGel®

Declaration of Performance N° CPR-IT045

Regulation (EU) n. 305/2011 - Regulation (EU) n. 574/2014

1. Unique identification code of the product-type:

FastGel

2. Intended use/es:

Improved fast-setting cementitious adhesive for indoor and outdoor installation, on walls and floors

3. Manufacturer:

LITOKOL LAB S.p.A. – Via G. Falcone 13/1 – 42048 Rubiera (RE) – Italy – www.litokol.com

4. System/s of AVCP:

System 3

5. Harmonised standard:

EN 12004:2007+A1:2012

Notified body/ies:

MCP Modena Centro Prove s.r.l. – NB 1599

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class E
Early tensile adhesion strength	≥ 0,5 N/mm^2
Initial tensile adhesion strength	≥ 1 N/mm^2
Tensile adhesion strength after water immersion	≥ 1 N/mm^2
Tensile adhesion strength after heat ageing	≥ 1 N/mm^2
Tensile adhesion strength after freeze-thaw cycles	≥ 1 N/mm^2
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Gian Luca Sghedoni – CEO Litokol Lab S.p.A.

Revision **n° 0**
Date: **14/01/26**