
Pixel® 3D-N

Technical Specifications



Pro Stain-Resistant Sealant. For bathrooms, shower cubicles, sanitary ware, kitchens, glass panels, window frames, doors and sealing delicate materials such as marble and natural stone.

Product description

Professional stain-resistant sealant with neutral curing properties for sealing permanently elastic joints between marble, granite, natural stone, tiles, porcelain stoneware, slabs and mosaics, both indoors and outdoors, on floors and walls.

Formulated for application without the need for any adhesion-promoting primer, it provides a perfect seal in bathrooms, shower cubicles, sanitary facilities, kitchens, glazed areas, window frames and doors.

Suitable for sealing expansion joints, even under severe operating conditions such as in swimming pools and on façades.

Chemistry + Smart

Free from solvents and isocyanates.

Not hazardous to applicators according to the CLP Regulation

Ready to use, reusable, minimises waste and material wastage.

Very low emissions of volatile organic compounds (VOCs)

Certifications

INT-EXT CC EN 15651-1

G CC EN 15651-2

S EN 15651-3

EC1 Plus Gev Eimcode

A+ Indoor air emissions

Materials

Marble and natural stone
Porcelain stoneware
Ceramic tiles
Resin- or cement-based composites
Terracotta – Klinker
Ceramic and glass mosaics
Sheets

Uses

Sealant
Floors – walls
Interior – exterior
Radiant heating systems
Indoor wet areas – bathrooms and showers
Ponds, swimming pools and fountains
Terraces and balconies
SPA and Hammam
Facades
Residential, public, commercial and street furniture

Limitations

Apply the product at temperatures between +5°C and +35°C
In hot weather, store the product packs in a cool place away from direct sunlight before use
Curing times are proportional to the thickness of the silicone joint
Avoid contact with bituminous materials or plasticisers, such as butyl, EPDM, neoprene, bituminous membranes and insulation materials
When refurbishing joints affected by mould, the existing elastic sealant must be completely removed
The product cannot be painted over.
Do not use for applications not listed on this Technical Data Sheet
For further information, please contact Litokol's Technical Customer Service on +39-0522-622811 or via customercare@litokol.com

Product specifications

Appearance	Thick paste
Colours	Transparent – Crystal
Responsible packaging	300 ml second-life recycled plastic cartridge
Customs classification	32149000
Shelf life	15 months in the original packaging, away from heat sources and direct light. Do not expose to frost.

Technical Specifications

Full curing	3 mm	24 hours
Shore A hardness	22	ISO 868
100% elastic modulus	$\geq 0.37 \text{ N/mm}^2$	ISO 8339
Elongation at break	300 %	ISO 8339
Tensile strength	$\geq 0.7 \text{ N/mm}^2$	ISO 8339
Total permissible deformation	25%	ASTM C920
Class	25 LM	ISO 11600 F

Application Specifications

Polymerisation	Neutral cross-linking
Consistency of the mix	Thixotropic paste
Specific gravity	1.02 kg/dm^3
Film formation time	About 25 minutes
Full cure in 24 hours	2–3 mm
Permissible application temperatures	From +5°C to +35°C
Recommended application temperatures	From +15°C to +25°C
Operating temperature	From -40°C to +150°C
Ready for foot traffic	24 hours at T = +23°C
Set-up time	5 days at T = +23°C

Application

Remove the top of the threaded section of the cartridge, screw on the plastic nozzle and cut it at an angle determined by the desired diameter and profile.

Insert the cartridge into the appropriate Power Gun and extrude the sealant, taking great care to avoid trapping air.

Once opened, the packs must be used up within a relatively short time.

The optimum working temperature for the substrate and sealant is between 15°C and 25°C.

Joint finishing must be carried out within the sealant's open time.

Avoid contact with solvents during curing.

Given the large number of factors affecting the processing and application of the product, the user should always carry out a test application.

Calculation of consumption

Linear metres of joint that can be achieved with a 300 ml cartridge					
	Width	Width	Width	Width	Width
Depth	6 mm	8 mm	10 mm	15 mm	20 mm
5 mm	$\pm 10 \text{ m}$	$\pm 8 \text{ m}$	$\pm 6 \text{ m}$	-	-
7 mm	-	$\pm 6 \text{ m}$	$\pm 4.5 \text{ m}$	$\pm 3 \text{ m}$	-
10 mm		-	$\pm 3 \text{ m}$	$\pm 2 \text{ m}$	$\pm 1.5 \text{ m}$
15 mm		-	-	$\pm 1.5 \text{ m}$	$\pm 1 \text{ m}$
20 mm		-	-	$\pm 1 \text{ m}$	$\pm 0.8 \text{ m}$

Safety Information

For the safe use of our products, please refer to the latest version of the Safety Data Sheet, available at www.litokol.com
PRODUCT FOR PROFESSIONAL USE

Legal notices

The information and specifications set out in this technical data sheet are based on our best knowledge.

However, as we are unable to directly influence site conditions or the execution of the works, these are general guidelines which do not in any way bind our Company.

We therefore recommend carrying out a preliminary test to verify the product's suitability for the intended use; in any case, anyone intending to use it is required to determine whether or not it is suitable for the intended use and, in any event, assumes all liability that may arise from its use.

Always refer to the latest updated version of the Technical Data Sheet, available on the website www.litokol.com

Product details **No. 843**

Revision **No. 0**

Date: **05 25**

Litokol

Litokol Lab Spa Via G. Falcone 13/1 42048 Rubiera RE Italy
Tel. +39 0522 622811 info@litokol.com www.litokol.com